

2 CORE AUTO CABLES (FLAT TWINS)

Manufactured in accordance with BS6862 Part 1 1971, where applicable.
Plain copper conductors - PVC insulated and sheathed.



PART No.	Conductor Specification (mm)	Conductor Cross Section (mm ²)	Current Rating (Amps)	Overall Diameter of Cable (mm)	Reel Sizes (Metres)
1649	2 x 9/0.30	2 x 0.65	5.75	6.1 x 3.8	30 100
1650	2 x 14/0.30	2 x 1.0	8.75	6.5 x 4.0	30 50 100
1651	2 x 21/0.30	2 x 1.5	12.75	7.3 x 4.5	30 100
1652	2 x 28/0.30	2 x 2.0	17.5	7.9 x 4.8	30 50 100
1653	2 x 35/0.30	2 x 2.5	21.75	9.1 x 5.6	30 100
1654	2 x 44/0.30	2 x 3.0	27.5	9.5 x 5.8	30 100
1655	2 x 65/0.30	2 x 4.5	35.0	10.5 x 6.3	30 100

4 CORE AUTO CABLES

Manufactured in accordance with BS6862 Part 1 1971, where applicable.
Plain copper conductors - PVC insulated and sheathed.



Part No	Conductor Specification (mm)	Conductor Cross Section (mm ²)	Current Rating (Amps)	Overall Diameter of Cable (mm)	Sheath Colour	Core Colours	Reel Sizes (Metres)
959	4 x 9/0.30	4 x 0.65	5.75	7.5	Black	Brown Green Red White	30 100
960	4 x 14/0.30	4 x 1.0	8.75	8.1	Black		30 100
961	4 x 21/0.30	4 x 1.5	12.75	9.0	Black		30 100

7 CORE AUTO CABLES

Manufactured in accordance with BS6862 Part 1 1971, where applicable.
Plain copper conductors - PVC insulated and sheathed.



Part No	Conductor Specification (mm)	Conductor Cross Section (mm ²)	Current Rating (Amps)	Overall Diameter of Cable (mm)	Sheath Colour	Core Colours	Reel Sizes (Metres)
953	7 x 16/0.20	7 x 0.5	4.25	8.5	Black	Black Red Green Yellow Brown White Blue	30 100
952	7 x 9/0.30	7 x 0.65	5.75	9.0	Black		30 100
954	7 x 14/0.30	7 x 1.0	8.75	9.5	Black		30 100
996	7 x 21/0.30	7 x 1.5	12.75	10.4	Black		30 100
955	6 x 9/0.30 1 x 14/0.30	6 x 0.65 1 x 1.0	6 x 5.75 1 x 8.75	9.2	Black		30 100
999	6 x 14/0.30 1 x 28/0.30	6 x 1.0 1 x 2.0	6 x 8.75 1 x 17.5	10.2	Black		30 100
1000	6 x 21/0.30 1 x 35/0.30	6 x 1.5 1 x 2.5	6 x 12.75 1 x 21.75	11.2	Grey		30 100